



## DECLARATION OF PERFORMANCE

### N° EN 1469 - 2020 - Vinalmont Limestone

1. Unique identification code of the product-type: **Vinalmont Limestone slabs for cladding**
2. Intended use: **Internal and external cladding according to EN 1469:2015 "Slabs for cladding"**
3. Address of the manufacturer:  
**Renier Natuursteen NV**  
Nijverheidslaan 1 - B-3200 Aarschot - Belgium  
+ 32 16 55 00 11 - info@renier.be  
www.renier.be
4. System of assessment and verification of constancy of the performance: **4**
5. Harmonized Standard: **EN1469:2015**  
Notified body: **none – see system 4**
6. Declared performances:

| Essential characteristics                                                    | Performances                                                                             |
|------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| Reaction to fire (internal use)                                              | <b>A1</b>                                                                                |
| Dangerous substances                                                         | <b>NPD</b>                                                                               |
| Water vapour permeability                                                    | <b>NPD</b>                                                                               |
| Flexural strength                                                            | <b>Lower expected value: 12,94 MPa<br/>Mean value: 21,6 MPa<br/>Std. deviation: 4,33</b> |
| Resistance to fixing                                                         | <b>Lower expected value: 1514 MPa<br/>Mean value: 1700 MPa<br/>Std. deviation: 93</b>    |
| Direct airborne sound insulation & thermal resistance                        | <b>NPD</b>                                                                               |
| Resistance to thermal shock ( <i>external use</i> )                          | <b>NPD</b>                                                                               |
| Emission of radioactivity                                                    | <b>NPD</b>                                                                               |
| Durability of flexural strength against freeze thaw ( <i>external use</i> )  | <b>NPD / NPD MPa</b>                                                                     |
| Resistance of marble to thermal and moisture cycling ( <i>external use</i> ) | <b>NPD</b>                                                                               |

The performance of the product identified above is in conformity with the set of declared performances.  
This declaration of performance is issued, in accordance with the Regulation (EU) n° 305/2011,  
under the sole responsibility of the manufacturer identified above.

Signed in Aarschot, on February 11<sup>th</sup> 2020 for and on behalf of the manufacturer by:

Stijn Renier  
For Pamoek BVBA  
General manager



\* E N 1 4 6 9 - C V C - E N U \*